




- NOTES
- APPLICABLE WIRE SIZE: CAVS 0.3~0.85, AVS 0.3~0.5
 ϕ 1.4~ ϕ 2.1
 - MATING FEMALE TERMINAL PART NO.: 7116-1680-08
- 注 記
- 適用電線サイズ: CAVS 0.3~0.85, AVS 0.3~0.5
 ϕ 1.4~ ϕ 2.1
 - 嵌合メス ターミナル品番: 7116-1680-08



ISSUE MARK

CUSTOMER		MATERIAL		COPPER ALLOY		TREAT.	
CUSTOMER PART NO.		SPEC.		T=0.25		GOLD PLATING	
OFFICE		NAME		SSD CONNECTOR			
VENDOR		TRIAL PART NO.		TERMINAL MALE(GOLD PLATING)			
VENDOR NO.		DWG TYPE		DWG SOURCE		PART NO.	
		R		NEW		7114-1680-08	
APPROVED		CHECKED		DESIGN		DRAWN	
91.07.11		91.07.11		ISHIZUKA		IMAMURA	
SPECIFIED		MASS		90.06.06		91.07.08	

GENERAL TOLERANCE							
	10MAX	50MAX	100MAX	250MAX	2500VR	ANGLE	ECCENT
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1
C	±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15

LET	DATE	REVISION RECORD	NO.	CHKD
	91.07.08	NEW	C91-6969	I. I