



注記

- 1. 適用電線サイズ : CAVS 0.3, CAVS 0.5, AVS 0.3
- △ 2. 材質 : C2600 t=0.30
- △ 仕様 : 金めっき
- △ 錫めっき
- △ 3. 適用ゴム栓品番 : 7157-3920-40
- △ 4. 相手端子品番 : 7116-4060-08

NOTES

- 1. APPLICABLE WIRE SIZE : CAVS 0.3, CAVS 0.5, AVS 0.3
- △ 2. MATERIAL : C2600 t=0.30
- △ TREATMENT : GOLD PLATING  
TIN PLATING
- △ 3. APPLICABLE RUBBER STOPPER NO. : 7157-3920-40
- △ 4. MATING PART NO. : 7116-4060-08

△	01.10.24	CHANGED TREATMENT NOTES, PART NAME & ADDED NOTE. □	C01-X908	E. F
△	98.08.04	CHANGED DIMENSION & NOTE	C97-N449	H. K
△	97.09.12	CHANGED PLATING	C97-M928	H. K
	97.07.28	NEW. □	C97-M548	M. T
LET	DATE	REVISION RECORD	NO.	CHKD

CUSTOMER		MATL. SPEC.	SEE NOTES	TREAT. & FIN.
CUSTOMER PART NO.				
OFFICE		NAME 050 SEALED TERMINAL MALE		
VENDOR		△ (GOLD PLATING)		
VENDOR NO.				

GENERAL TOLERANCE								VENDOR NO.					
	10MAX	50MAX	100MAX	250MAX	2500VR	ANGLE	ECCENT	DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1	R	NEW	97.07.28	mm	5/1	3
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN	
◎	±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15	所之内 川梨 繁福		S. KODAMA	ISHIJIMA		
SPECIFIED								MASS		9			

PART NO. 7114-4060-08, □		SET DWG NO.	
CH. CODE		7114-4060-08:R	
DWG NO.		7114-4060-08:R	
YAZAKI CORPORATION			

B

A

B

A