


RUBBER PART GENERAL TOLERANCE				
PART DIM.	1	2	③	
0 TO 3	± 0.2	± 0.3	± 0.4	
3 TO 6	± 0.2	± 0.4	± 0.5	
6 TO 10	± 0.3	± 0.5	± 0.6	
10 TO 18	± 0.3	± 0.6	± 0.8	
18 TO 30	± 0.4	± 0.8	± 1.0	
30 TO 50	± 0.5	± 1.0	± 1.5	
50 TO 80	± 0.6	± 1.2	± 2.0	
80 TO 120	± 0.7	± 1.4	± 2.5	
120 TO 180	± 0.8	± 1.6	± 3.0	
180 TO 250	± 1.0	± 2.0	± 4.0	
250 TO 315	± 1.2	± 2.5	± 5.0	
315 TO 400	± 1.5	± 3.0	± 6.0	
400 TO 500	± 1.8	± 3.5	± 7.0	
500 OVER	± 0.4 %	± 0.8 %	± 1.5 %	

B

A



ISSUE MARK

CUSTOMER										MATL. NBR(BLACK)			TREAT. & FIN.		
CUSTOMER PART NO.					CUSTOMER DWG NO.					NAME 312 PLUGGING RUBBER STOPPER					
89.09.25	NEW			C89-M006	H. Y	OFFICE	STDLIB NO.								
LET	DATE	REVISION RECORD			NO.	CHKD	VENDOR								
GENERAL TOLERANCE							VENDOR NO.								
10MAX	50MAX	100MAX	250MAX	250OVR	ANGLE	ECCENT	DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE	PART NO. 7157-8764		
A ±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1	R	NEW	89.09.25	mm	5/1	3	DWG NO. 7157-8764:R		
B ±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN		TRIAL PART NO. 7F8957-6552		
C ±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15	加藤 福田 辻			M. TSUJI	S. INABA		YAZAKI CORPORATION		
SPECIFIED RUBBER PART GENERAL TOLERANCE 1						WEIGHT	9 89.10.03 89.10.02 89.10.02 89.08.19 89.09.25								