



SEC. A-A

RUBBER PART		GENERAL TOLERANCE		
PART DIM.		1	2	③
0 TO 3		±0.2	±0.3	±0.4
3 TO 6		±0.2	±0.4	±0.5
6 TO 10		±0.3	±0.5	±0.6
10 TO 18		±0.3	±0.6	±0.8
18 TO 30		±0.4	±0.8	±1.0
30 TO 50		±0.5	±1.0	±1.5
50 TO 80		±0.6	±1.2	±2.0
80 TO 120		±0.7	±1.4	±2.5
120 TO 180		±0.8	±1.6	±3.0
180 TO 250		±1.0	±2.0	±4.0
250 TO 315		±1.2	±2.5	±5.0
315 TO 400		±1.5	±3.0	±6.0
400 TO 500		±1.8	±3.5	±7.0
500 OVER		±0.4 %	±0.8 %	±1.5 %

注記

- △ 1. 適用電線サイズ : AVSS/CAVS 0.3~0.85
- AVSSX/AESSX 0.5~0.75
- CHFUS 0.35~0.75
- CIVUS 0.35~1.25
- HFSS 0.5
- IVSSH 0.35f~0.75f

NOTE

- △ 1. APPLICABLE WIRE SIZE : AVSS/CAVS 0.3~0.85
- AVSSX/AESSX 0.5~0.75
- CHFUS 0.35~0.75
- CIVUS 0.35~1.25
- HFSS 0.5
- IVSSH 0.35f~0.75f

ISSUE MARK

△ 2018/09/10		ADDED APPLICABLE WIRE SIZE, ETC.		C18-P257	Y. M	CUSTOMER				MATL. SILICONE RUBBER		TREAT. & FIN.			
1995/11/02		NEW		C95-M403	K. O	CUSTOMER PART NO.				SPEC. (BLUE)					
LET DATE		REVISION RECORD		NO.	CHKD	CUSTOMER DWG NO.				NAME △ 2.3 II 5mm pitch RUBBER					
						OFFICE				TRIAL PART NO. or PRODUCT NO.					
						VENDOR				STOPPER (S SIZE)					
						VENDOR NO.				PART NO. 7158-3003-90					
						GENERAL TOLERANCE				CH. CODE 7158-3003-90					
	10MAX	50MAX	100MAX	250MAX	250OVR	ANGLE	ECCENT	DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE	DWG NO.	SET DWG NO.
A	±0.15	±0.2	±0.3	±0.5	±0.75	±0.5°	0.1	R	NEW	1995/11/02	mm	10:1	3	7158-3003-90:R	
B	±0.2	±0.3	±0.55	±0.95	±1.4	±1.0°	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN			
C	±0.3	±0.5	±0.8	±1.4	±2	±1.5°	0.15	N. TAGUCHI	K. FUKUDA		MAEDA	Y. MAEDA			
SPECIFIED				MASS		△ (0.2) g		2018/09/10		2018/09/10		1994/09/27		2018/09/10	

YAZAKI Corporation