



SEC. A-A

RUBBER PART		GENERAL TOLERANCE		
PART DIM.		1	2	③
0 TO 3		±0.2	±0.3	±0.4
3 TO 6		±0.2	±0.4	±0.5
6 TO 10		±0.3	±0.5	±0.6
10 TO 18		±0.3	±0.6	±0.8
18 TO 30		±0.4	±0.8	±1.0
30 TO 50		±0.5	±1.0	±1.5
50 TO 80		±0.6	±1.2	±2.0
80 TO 120		±0.7	±1.4	±2.5
120 TO 180		±0.8	±1.6	±3.0
180 TO 250		±1.0	±2.0	±4.0
250 TO 315		±1.2	±2.5	±5.0
315 TO 400		±1.5	±3.0	±6.0
400 TO 500		±1.8	±3.5	±7.0
500 OVER		±0.4 %	±0.8 %	±1.5 %

注記

- △ 1. 適用電線サイズ : AVS 0.5~0.85
 AVSS/CAVS/IVSSH 1.25
 CHFUS/CIVUS 1.5

NOTE

- △ 1. APPLICABLE WIRE SIZE : AVS 0.5~0.85
 AVSS/CAVS/IVSSH 1.25
 CHFUS/CIVUS 1.5

ISSUE MARK

△	2018/09/10	ADDED APPLICABLE WIRE SIZE, ETC.	C18-P257	Y. M	CUSTOMER				MATL. SILICONE RUBBER	TREAT. & FIN.				
	1995/10/23	NEW	C95-M403	K. O	CUSTOMER PART NO.				SPEC. (GRAY)					
LET	DATE	REVISION RECORD	NO.	CHKD	CUSTOMER DWG NO.				NAME △ 2.3 II 5mm pitch RUBBER					
GENERAL TOLERANCE					OFFICE				TRIAL PART NO. or PRODUCT NO.					
					VENDOR				STOPPER (M SIZE)					
					VENDOR NO.				PART NO. 7158-3004-40					
A	±0.15	±0.2	±0.3	±0.5	±0.75	±0.5°	0.1	DWG TYPE R	DWG SOURCE NEW	DWG DATE 1995/10/23	UNIT mm	SCL 10:1	ANGLE 3	CH. CODE
B	±0.2	±0.3	±0.55	±0.95	±1.4	±1.0°	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN	DWG NO. 7158-3004-40:R	SET DWG NO.
C	±0.3	±0.5	±0.8	±1.4	±2	±1.5°	0.15	N. TAGUCHI	K. FUKUDA		MAEDA	Y. MAEDA	YAZAKI Corporation	
SPECIFIED					MASS △ (0.2) g				2018/09/10				2018/09/10	