



SEC. A-A

RUBBER PART		GENERAL TOLERANCE		
PART DIM.		1	2	③
0 TO 3		±0.2	±0.3	±0.4
3 TO 6		±0.2	±0.4	±0.5
6 TO 10		±0.3	±0.5	±0.6
10 TO 18		±0.3	±0.6	±0.8
18 TO 30		±0.4	±0.8	±1.0
30 TO 50		±0.5	±1.0	±1.5
50 TO 80		±0.6	±1.2	±2.0
80 TO 120		±0.7	±1.4	±2.5
120 TO 180		±0.8	±1.6	±3.0
180 TO 250		±1.0	±2.0	±4.0
250 TO 315		±1.2	±2.5	±5.0
315 TO 400		±1.5	±3.0	±6.0
400 TO 500		±1.8	±3.5	±7.0
500 OVER		±0.4 %	±0.8 %	±1.5 %

注記

- △ 1. 適用電線サイズ : AVSS 2  
 AVSSH/AVSSX 2  
 HFSS 2  
 IVSSH 2f

NOTE

- △ 1. APPLICABLE WIRE SIZE : AVSS 2  
 AVSSH/AVSSX 2  
 HFSS 2  
 IVSSH 2f

ISSUE MARK

△	2018/09/10	ADDED APPLICABLE WIRE SIZE, ETC.	C18-P257	Y. M	CUSTOMER	MATL. SILICONE RUBBER	TREAT. & FIN.
△	2003/06/03	CHANGED NOTES	C03-X350	H. T	CUSTOMER PART NO.	SPEC. (BROWN)	
	1995/10/23	NEW	C95-M403	K. O	CUSTOMER DWG NO.	NAME △ 2.3 II 5mm pitch RUBBER	
LET	DATE	REVISION RECORD	NO.	CHKD	OFFICE	STOPPER (L SIZE)	
GENERAL TOLERANCE					VENDOR	PART NO. 7158-3005-80	
	10MAX	50MAX	100MAX	250MAX	250OVR	ANGLE	ECCENT
A	±0.15	±0.2	±0.3	±0.5	±0.75	±0.5°	0.1
B	±0.2	±0.3	±0.55	±0.95	±1.4	±1.0°	0.1
C	±0.3	±0.5	±0.8	±1.4	±2	±1.5°	0.15
SPECIFIED					MASS	CH. CODE 7158-3005-80	
					△ (0.1) g	APPROVED	DESIGN
						N. TAGUCHI	MAEDA
						K. FUKUDA	Y. MAEDA
						2018/09/10	1994/09/27
						2018/09/10	2018/09/10
						DWG NO. 7158-3005-80:R	
						SET DWG NO.	
<b>YAZAKI Corporation</b>							