



SEC. A-A

RUBBER PART GENERAL TOLERANCE			
PART DIM.	1	2	③
0 TO 3	± 0.2	± 0.3	± 0.4
3 TO 6	± 0.2	± 0.4	± 0.5
6 TO 10	± 0.3	± 0.5	± 0.6
10 TO 18	± 0.3	± 0.6	± 0.8
18 TO 30	± 0.4	± 0.8	± 1.0
30 TO 50	± 0.5	± 1.0	± 1.5
50 TO 80	± 0.6	± 1.2	± 2.0
80 TO 120	± 0.7	± 1.4	± 2.5
120 TO 180	± 0.8	± 1.6	± 3.0
180 TO 250	± 1.0	± 2.0	± 4.0
250 TO 315	± 1.2	± 2.5	± 5.0
315 TO 400	± 1.5	± 3.0	± 6.0
400 TO 500	± 1.8	± 3.5	± 7.0
500 OVER	± 0.4 %	± 0.8 %	± 1.5 %

注記

1. 適用電線サイズ : 標準仕上り外径 ϕ 3.60とする。

NOTE

1. APPLICABLE WIRE SIZE : NOMINAL DIAMETER OF FINISHED CABLE ϕ 3.60.

ISSUE MARK

CUSTOMER										MATL. SILICONE RUBBER			TREAT. & FIN.		
CUSTOMER PART NO.					CUSTOMER DWG NO.					SPEC. (DARK BROWN)					
OFFICE										NAME 312 RUBBER STOPPER					
VENDOR										TRIAL PART NO.					
VENDOR NO.										(L SIZE)					
GENERAL TOLERANCE										PART NO. 7158-3022-80, A					
10MAX	50MAX	100MAX	250MAX	250OVR	ANGLE	ECCENT	DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE	CH. CODE		
A	±0.15	±0.2	±0.3	±0.5	±30'	0.1	R	NEW	95.10.23	mm	5/1	3	7158-3022-80:R		
B	±0.2	±0.3	±0.55	±0.95	±30'	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN		DWG NO.		
C	±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15	手倉	福平	山崎 裕	MAEDA	SAMUKAWA		7158-3022-80:R	
SPECIFIED					MASS					YAZAKI CORPORATION					
					g 95.11.13 95.12.31 95.10.30 94.09.15 95.10.23										