



SEC. A-A

RUBBER PART GENERAL TOLERANCE				
PART DIM.	1	2	③	
0 TO 3	± 0.2	± 0.3	± 0.4	
3 TO 6	± 0.2	± 0.4	± 0.5	
6 TO 10	± 0.3	± 0.5	± 0.6	
10 TO 18	± 0.3	± 0.6	± 0.8	
18 TO 30	± 0.4	± 0.8	± 1.0	
30 TO 50	± 0.5	± 1.0	± 1.5	
50 TO 80	± 0.6	± 1.2	± 2.0	
80 TO 120	± 0.7	± 1.4	± 2.5	
120 TO 180	± 0.8	± 1.6	± 3.0	
180 TO 250	± 1.0	± 2.0	± 4.0	
250 TO 315	± 1.2	± 2.5	± 5.0	
315 TO 400	± 1.5	± 3.0	± 6.0	
400 TO 500	± 1.8	± 3.5	± 7.0	
500 OVER	± 0.4 %	± 0.8 %	± 1.5 %	

注記

- △ 1. 適用電線サイズ : AVS 5.0
AVX 5.0
AEX 5.0

NOTE

- △ 1. APPLICABLE WIRE SIZE : AVS 5.0
AVX 5.0
AEX 5.0

ISSUE MARK

				CUSTOMER				MATERIAL SPEC.				SILICONE RUBBER (BLACK)				TREAT. & FIN.													
△ 2018/04/18				ADDED APPLICABLE WIRE SIZE, ETC.				C18-Z059				A. Q																	
1995/10/23				NEW. [A]				C95-M403				K. O																	
LET				DATE				REVISION RECORD				NO.				CHKD													
GENERAL TOLERANCE																													
10MAX		50MAX		100MAX		250MAX		250QVR		ANGLE		ECCENT		DWG TYPE		DWG SOURCE		DWG DATE		UNIT		SCL		ANGLE					
A		±0.15		±0.2		±0.3		±0.5		±0.75		±30'		0.1		R		NEW		1995/10/23		mm		5:1		3			
B		±0.2		±0.3		±0.55		±0.95		±1.4		±30'		0.1		APPROVED		CHECKED		CHECKED		DESIGN		DRAWN					
C		±0.3		±0.5		±0.8		±1.4		±2		±30'		0.15		N. TAGUCHI		K. FUKUDA				MAEDA		A. QUIROL					
SPECIFIED										MASS						2018/04/18		2018/04/18				1994/09/15		2018/04/18		PART NO. 7158-3023, [A]			
																DWG NO. 7158-3023:R				SET DWG NO.									
																YAZAKI CORPORATION													