



△ TABLE 1

SUB ASSEMBLY PART NO. AND CH. CODE	NO.	PART NO. AND CH. CODE	MATERIAL	COLOR	△ QTY.
7282-1065 ETC.	①	SEE TABLE 2	△ PBT	SEE TABLE 2	1
	②	7157-4041	△ PBT	△ NATURAL	1

△ TABLE 2

SUB ASSEMBLY PART NO. AND CH. CODE	PART NO. AND CH. CODE	COLOR
7282-1065.△	7182-1065	NATURAL
7282-1065-10.△	7182-1065-10	DARK GRAY
7282-1065-30.△	7182-1065-30	BLACK
7282-1065-40.△	7182-1065-40	LIGHT GRAY
7282-1065-50.△	7182-1065-50	ORANGE
7282-1065-90.△	7182-1065-90	BLUE

注記

- 1. 嵌合相手品番：7283-1065 ETC.
- 2. 適用端子品番：7114-4030 ETC.

NOTES

- 1. MATING PART NO. :7283-1065 ETC.
- 2. APPLICABLE TERMINAL NO. :7114-4030 ETC.

△	99.02.11	ELIMINATED COLOR NO. & CHANGED MATERIAL	C99-L397	T.M	CUSTOMER				MATL. SPEC.		TREAT. & FIN.		ISSUE MARK								
△	96.07.01	CHANGED MATERIAL & ADDED PART NO. △	C96-M112	A.Y	CUSTOMER PART NO.				CUSTOMER DWG NO.												
	89.07.19	NEW	C89-L353	H.I	OFFICE				TRIAL PART NO.		NAME 187 6P CONNECTOR										
LET	DATE	REVISION RECORD	NO.	CHKD	VENDOR				VENDOR NO.		SUB ASSEMBLY MALE										
GENERAL TOLERANCE					DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE	PART NO. 7282-1065 ETC.										
	10MAX	50MAX	100MAX	250MAX	250QVR	ANGLE	ECCENT				CH. CODE										
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1	R	NEW	89.07.19	mm	1/2	3								
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN	DWG NO. 7282-1065:R								
◎	±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15	加藤	小梨	藤	Y. OHTA	KANAZAWA	SET DWG NO.								
SPECIFIED					MASS	g				199.03.11		99.03.04		99.03.02		88.11.30		99.02.11		YAZAKI CORPORATION	