



SUB ASSEMBLY PART NO.	NO.	PART NO.	MATERIAL	COLOR	QTY.
7283-1074-40. A	①	7183-1074-40.	PBT	LIGHT GRAY	1
	②	7157-6503	PBT	NATURAL	1

注記

- 1. 嵌合相手品番 : 7282-1074-40
- 2. 通用端子品番 : 090II 7116-4025 ETC.
- 3. 通用ゴム栓品番 : 090II 7158-3006-90 ETC.

NOTES

- 1. MATING PART NO. : 7282-1074-40
- 2. APPLICABLE TERMINAL NO. :
:090II 7116-4025 ETC.
- 3. APPLICABLE RUBBER STOPPER NO. :
:090II 7158-3006-90 ETC.

△	08.02.15	CORRECTION OF CLERICAL ERROR	C08-Z091	S. S	CUSTOMER	MATL. SPEC.	SEE TABLE	TREAT. & FIN.	ISSUE MARK						
△	98.03.16	CHANGED FORM. A	C98-L440	N. T	CUSTOMER PART NO.										
	93.08.07	NEW	C93-L849	H. F	CUSTOMER DWG NO.			NAME 312 2P+187 3P+090II 12P LIF SEALED							
LET	DATE	REVISION RECORD	NO.	CHKD	OFFICE	TRIAL PART NO.		CONNECTOR HOUSING FEMALE SUB ASSEMBLY							
GENERAL TOLERANCE					VENDOR NO.										
	10MAX	50MAX	100MAX	250MAX	2500VR	ANGLE	ECCENT	DWG TYPE	DWG SOURCE	DWG DATE	UNIT	SCL	ANGLE	PART NO.	7283-1074-40. A
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1	R	NEW	93.08.07	mm	2:1	3	CH. CODE	7283-1074-40. A
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	APPROVED	CHECKED	CHECKED	DESIGN	DRAWN	DWG NO.	7283-1074-40:R	SET DWG NO.
C	±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15	山梨 鈴木			A. SHINCHI	M. MORAL	YAZAKI CORPORATION		
SPECIFIED					MASS	g		'08.2.18		'08.02.15	92.09.16	08.02.15			