


SEC. B-B



SEC. A-A

△TABLE 1

| SUB ASSEMBLY PART NO. AND CH. CODE | NO. | PART NO. AND CH. CODE | PART NAME | MATERIAL | COLOR | QTY. |
|------------------------------------|-----|-----------------------|--------------------------------|----------|-------------|------|
| 7283-1132 ETC. | ① | SEE TABLE 2 | 2.3II 3P HOUSING FEMALE | PBT | SEE TABLE 2 | 1 |
| | ② | 7157-4351 | 2.3II 3P HOUSING SPACER FEMALE | PBT | NATURAL | 1 |

△TABLE 2

| SUB ASSEMBLY PART NO. AND CH. CODE | PART NO. AND CH. CODE | COLOR |
|------------------------------------|-----------------------|------------|
| △ 7283-1132, ▢ | 7183-1132 | NATURAL |
| △ 7283-1132-10, ▢ | 7183-1132-10 | DARK GRAY |
| △ 7283-1132-30, ▢ | 7183-1132-30 | BLACK |
| △ 7283-1132-40, ▢ | 7183-1132-40 | LIGHT GRAY |
| △ 7283-1132-50, ▢ | 7183-1132-50 | ORANGE |
| △ 7283-1132-60, ▢ | 7183-1132-60 | GREEN |
| △ 7283-1132-80, ▢ | 7183-1132-80 | BROWN |
| △ 7283-1132-90, ▢ | 7183-1132-90 | BLUE |

注記

△ 1. 取扱説明書No. YPES-15-080

NOTE

△ 1. HANDLING MANUAL NO. YPES-15-080

ISSUE MARK

| | | | | | | | | | | | | | | | | |
|-------------------|---------------------------|---------------------|--------|------------|-------------------|------------------|---------------------|--------------------|---------------|------------|----------|-----------|--------------------|-------------|----------------|--|
| △ 10.11.04 | CHANGED PART NAME ETC., ▢ | C10-Z553 | T. S | CUSTOMER | CUSTOMER PART NO. | CUSTOMER DWG NO. | MATL. SPEC. | △ SEE TABLE 1 | TREAT. & FIN. | | | | | | | |
| 90.11.10 | NEW | C90-M212 | M. H | OFFICE | TRIAL PART NO. | | NAME | △ 2.3II 3P HOUSING | | | | | | | | |
| LET | DATE | REVISION RECORD NO. | CHKD | VENDOR | | | SUB ASSEMBLY FEMALE | | | | | | | | | |
| GENERAL TOLERANCE | | | | VENDOR NO. | | | | | | | | | | | | |
| | 10MAX | 50MAX | 100MAX | 250MAX | 2500VR | ANGLE | ECCENT | DWG TYPE | DWG SOURCE | DWG DATE | UNIT | SCL | ANGLE | PART NO. | 7283-1132 ETC. | |
| A | ±0.15 | ±0.2 | ±0.3 | ±0.5 | ±0.75 | ±30' | 0.1 | R | NEW | 90.11.10 | mm | 2:1 | 3 | CH. CODE | 7283-1132 ETC. | |
| B | ±0.2 | ±0.3 | ±0.55 | ±0.95 | ±1.4 | ±30' | 0.1 | APPROVED | CHECKED | CHECKED | DESIGN | DRAWN | DWG NO. | 7283-1132:R | SET DWG NO. | |
| (C) | ±0.3 | ±0.5 | ±0.8 | ±1.4 | ±2 | ±30' | 0.15 | M. FUKUDA | O. SUGIYAMA | T. SHIMIZU | Y. OHTA | J. GAMBOA | YAZAKI CORPORATION | | | |
| SPECIFIED | | | | MASS | | | 10.11.04 | | | 10.11.04 | 10.11.04 | 88.10.31 | 10.11.04 | | | |