

SEC. A-A

TABLE 1

SUB ASSEMBLY PART NO. AND CH. CODE	NO.	PART NO. AND CH. CODE	PART NAME	MATERIAL	COLOR	QTY.
7283-1160 ETC.	①	SEE TABLE 2	2.3II 16P HOUSING FEMALE	PBT	SEE TABLE 2	1
	②	7157-4033	2.3II 16P SPACER FEMALE	PBT	NATURAL	1

TABLE 2


SUB ASSEMBLY PART NO. AND CH. CODE	PART NO. AND CH. CODE	COLOR
7283-1160.□	7183-1160	NATURAL
7283-1160-10.□	7183-1160-10	DARK GRAY
7283-1160-30.□	7183-1160-30	BLACK
7283-1160-40.□	7183-1160-40	LIGHT GRAY
7283-1160-90.□	7183-1160-90	BLUE

NOTES

- MATING PART NO. : 7282-1160 ETC.
- APPLICABLE TERMINAL NO. : 7116-4020, 7116-4021, 7116-4022
- HANDLING MANUAL NO. : YPES-15-080

注記

- かん合相手品番 : 7282-1160 ETC.
- 適用端子品番 : 7116-4020, 7116-4021, 7116-4022
- 取扱説明書NO. : YPES-15-080



ISSUE MARK

DATE	REVISION RECORD	NO.	CHKD
2019/03/13	CHANGED MATERIAL, ETC.	C19-Z030	A. S
1998/12/23	ELIMINATED COLOR NO.	C98-N184	T. M
1997/06/19	ADDED PART NO. & CHANGED MATERIAL.□	C97-M141	M. T
1990/11/10	NEW	C90-M213	M. H

CUSTOMER	CUSTOMER PART NO.	CUSTOMER DWG NO.
OFFICE	TRIAL PART NO.	
VENDOR	VENDOR NO.	

MATL. SPEC.	SEE TABLE 1	TREAT. & FIN.
NAME		
2.3II 16P HOUSING		
SUB ASSEMBLY FEMALE		
PART NO. CH. CODE	7283-1160 ETC.	
DWG NO.	7283-1160:R	SET DWG NO.
	YAZAKI CORPORATION	

GENERAL TOLERANCE							
	10MAX	50MAX	100MAX	250MAX	250OVR	ANGLE	ECCENT
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1
◎	±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15

SPECIFIED	MASS
	△(5.6)g