


SECTION A-A

TYPE A	TYPE B
7283-6443-40	7283-6444-60
7283-6443-50	7283-6444-70
△ 7283-6443	

SUB ASSEMBLY PART NO.	NO.	PART NO.	PART NAME	MATERIAL	COLOR	QTY.	YAZAKI MATING PART NO.
7283-6443-40	①	7183-6443-40	1.5 SYSTEM CONNECTOR 2P (F) HOUSING (TYPE A)	PBT-GF15	LIGHT GREY	1	7282-6443-40
	②	7158-5970	1.5 SYSTEM CONNECTOR 2P (F) FRONT HOLDER	PBT	NATURAL	1	
7283-6443-50	①	7183-6443-50	1.5 SYSTEM CONNECTOR 2P (F) HOUSING (TYPE A)	PBT-GF15	ORANGE	1	△ 7282-6443-50
	②	7158-5970	1.5 SYSTEM CONNECTOR 2P (F) FRONT HOLDER	PBT	NATURAL	1	
7283-6443	①	7183-6443	1.5 SYSTEM CONNECTOR 2P (F) HOUSING (TYPE A)	PBT-GF15	NATURAL	1	7282-6443
	②	7158-5970-30	1.5 SYSTEM CONNECTOR 2P (F) FRONT HOLDER	PBT	BLACK	1	
7283-6444-60	①	7183-6444-60	1.5 SYSTEM CONNECTOR 2P (F) HOUSING (TYPE B)	PBT-GF15	GREEN	1	7282-6444-60
	②	7158-5970	1.5 SYSTEM CONNECTOR 2P (F) FRONT HOLDER	PBT	NATURAL	1	
7283-6444-70	①	7183-6444-70	1.5 SYSTEM CONNECTOR 2P (F) HOUSING (TYPE B)	PBT-GF15	YELLOW	1	△ 7282-6444-70
	②	7158-5970	1.5 SYSTEM CONNECTOR 2P (F) FRONT HOLDER	PBT	NATURAL	1	

△ NOTES

1. MATERIAL: SEE TABLE.
2. COLOR: SEE TABLE.
3. APPLICABLE TERMINAL PART NO.: 7116-4100-02 ETC.
4. MATING PART NO.: SEE TABLE.
5. FOR GENERAL GEOMETRICAL TOLERANCE SEE TABLE (ECCENT=ECCENTRICITY).
6. HANDLING MANUAL: YPES-15-599.



ISOMETRIC VIEW

(SCALE 1:1)

ISSUE MARK

CUSTOMER		MATERIAL SPEC.		TREAT. & FIN.	
CUSTOMER PART NO.		SEE TABLE			
CUSTOMER DWG NO.		NAME		1.5 SYSTEM CONNECTOR	
OFFICE		TRIAL PART NO.		2P (F) SUB ASS' Y (TYPE A&B)	
VENDOR		VENDOR NO.		PART NO. 7283-6443-40, ETC.	
DWG TYPE		DWG SOURCE		CH. CODE	
R		NEW		7283-6443-40:R	
DWG DATE		UNIT		SET DWG NO.	
14/10/02		mm			
SCL		ANGLE		YAZAKI CORPORATION	
2/1		3			
APPROVED		CHECKED		DESIGN	
H. LUTSEH		R. BESMAN		DRAWN	
M. KASHIYAMA		G. GREGURIC		G. GREGURIC	
06/10/02		05/02/07		02/02/07	
06/08/02		02/02/07		02/02/07	

LET	DATE	REVISION RECORD	NO.	CHKD
△	07/02/02	ADDED PART NUMBER & CHANGED NOTES	C07-D533	G. G.
△	02/06/12	NEW	C02-E147	S. T.

GENERAL TOLERANCE								
	10MAX	50MAX	100MAX	250MAX	2500VR	ANGLE	ECCENT	
A	±0.15	±0.2	±0.3	±0.5	±0.75	±30'	0.1	
B	±0.2	±0.3	±0.55	±0.95	±1.4	±30'	0.1	
C	±0.3	±0.5	±0.8	±1.4	±2	±30'	0.15	
SPECIFIED							MASS	2.9 g
The materials used in this product are in conformity with requirements of EU ENEC 2000/53/EC directive and associated documents.								

1

2

3

4

5

A2